


kvs

„Hydromat DTR“ (

PN 16

(: „Hydromat DP“)

(VDI 2035).



EN 10226

: 50 300


15	2,5	106 45 04
20	5,0	106 45 06
25	7,5	106 45 08
32	10,0	106 45 10
40	15,0	106 45 12
50	34,0	106 45 16

Oventrop

EN 10226

: 250 700

15	2,5	106 47 04
20	5,0	106 47 06
25	7,5	106 47 08
32	10,0	106 47 10
40	15,0	106 47 12
50	34,0	106 47 16



: 50 300

15	2,5	106 46 04
20	5,0	106 46 06
25	7,5	106 46 08
32	10,0	106 46 10
40	15,0	106 46 12
50	34,0	106 46 16

: 250 700

15	2,5	106 48 04
20	5,0	106 48 06
25	7,5	106 48 08
32	10,0	106 48 10
40	15,0	106 48 12
50	34,0	106 48 16

- G 3/4
- G 1
- G 1 1/4
- G 1 1/2
- G 1 3/4
- G 2 3/8

„Hydromat DTR“
: 16 (PN 16)
: -10°C 120°C

EPDM.

EPDM.

15 20

: 102 71 . . . 3.35.

„Hydromat DFC“
: 16 (PN 16)
: -10°C 120°C

(EN-GJL-250 DIN EN 1561).

DIN EN 558-1.

EPDM.

EPDM.