







DIN-EN-ISO 6806

		DIN-EN-ISO 6806			
	NI 8	500 750 1000 1250 1500	G 3/8	90°	211 00 51
					211 00 52
					211 00 53
					211 00 54
					211 00 55
	NI 12,5	750 1000 1250 1500	G 1/2	90°	211 00 56
					211 00 57
					211 00 58
					211 00 59
	NI 8	500 750 1000 1250 1500	G 3/8, G 3/8	90°	211 00 71
					211 00 72
					211 00 73
	NI 8	500 750 1000 1250 1500	NPT 1/4, G 3/8	90°	211 01 51
					211 01 52
					211 01 53
					211 01 54
					211 01 55
	NI 8	300 500 750 1000 1250 1500	G 3/8, G 1/4	90°	211 02 51
					211 02 52
					211 02 53
					211 02 54
					211 02 55
	NI 8 8 x 8	300 500 750 1000	G 3/8	90°	211 03 50
					211 03 51
					211 03 52
	NI 10 10 x 10	300 500 750 1000	G 3/8	90°	211 03 53
					211 03 54
					211 03 55
	NI 10 12 x 12	300 500 750 1000	G 3/8	90°	211 05 51
					211 05 52
					211 05 53
					211 05 54
					211 05 55
					211 05 56
					EL DIN 4755.
					PN 10, 70 °C.
					DIN-EN-ISO 6806
					DIN 4798
					NI 8 6
					NI 10 8
					NI 12,5 10
					. 9.10.
					.9.38