


„Copipe HS“



14 x 2,0
50
100
200

150 10 54
150 01 54
150 02 54

16 (PN 16)
DVGW- DW-8501AT2407

: 10 95 °C

16 x 2,0
50
100
200
500

150 10 55
150 01 55
150 02 55
150 05 55

18 x 2,0
100

150 01 58

20 x 2,5
50
100

150 10 60
150 01 60

26 x 3,0
50

150 10 66

32 x 3,0
50

150 10 72

4
50

4

16 x 2,0
20 x 2,5

150 11 55
150 11 60

DIN 1988.


6
50

6

16 x 2,0
20 x 2,5

150 13 55
150 13 60

DIN 1988.




9
50

9

16 x 2,0
20 x 2,5


150 14 55
150 14 60



50

14 x 2,0
16 x 2,0
20 x 2,5

150 12 54
150 12 55
150 12 60



20

: 5
16x2,0
**

150 15 55

R90

„Copipe HS“:

13

20x2,5
**

150 15 60

– Curaflam-Tape MP Doyma

7

26x3,0
**

150 15 66

– Conlit 150 RS 800

5

32x3,0
**

150 15 72

835 Rockwool.

9

40x3,5
**

150 15 80

4

50x4,5
**

150 15 82

3

63x6,0
**

150 15 84

Pragothem Prag

**