


„Combi 2”


EN 10226-1

: 10 (PN 10)
: 2°C - 120°C
130°C).


DIN 3842.




| | | | |
|----|-----|------|------------------|
| 10 | 1,7 | (25) | 109 10 61 |
| 15 | 1,7 | (25) | 109 10 62 |
| 20 | 1,7 | (10) | 109 10 63 |



| | | | |
|---------------|-----|------|------------------|
| 15 | 1,7 | (25) | 109 10 72 |
| G 3/4 x G 1/2 | | | |




| | | | |
|----|-----|------|------------------|
| 10 | 1,7 | (25) | 109 11 61 |
| 15 | 1,7 | (25) | 109 11 62 |
| 20 | 1,7 | (10) | 109 11 63 |



| | | | |
|---------------|-----|------|------------------|
| 15 | 1,7 | (25) | 109 11 72 |
| G 3/4 x G 1/2 | | | |

/ ,



| | | | |
|------------|-----|------|------------------|
| R 3/8 x 12 | 1,7 | (25) | 109 12 51 |
| R 1/2 x 12 | 1,7 | (25) | 109 12 52 |
| R 1/2 x 15 | 1,7 | (25) | 109 12 53 |

| | | | |
|------------|-----|------|------------------|
| R 3/8 x 12 | 1,7 | (25) | 109 13 51 |
|------------|-----|------|------------------|